

OPTICAL APPARATUSES USING THE NEAR-FIELD LIGHT

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to optical apparatuses that uses the near-field light, such as optical microscopes, optical measurement instruments, spectroscopic instruments, optical recording/reproduction apparatuses all of which use the near-field light.

2. Description of Related Art

In the conventional optical microscope, light is focused with lenses. In this case, spatial resolution is limited by light wavelength.

On the other hand, the near-field optical microscope uses a probe having a microstructure whose dimensions are of an order of nanometer, for example a micro aperture whose diameter is of an order of nanometer. When the microstructure is irradiated with light, localized light called near-field light is generated in the vicinity thereof. If the microstructure is brought close to a sample and the object (the sample) is illuminated with the near-field light, the localized near-field light is converted to propagating light, depending on the complex

2025-01-16 09:00:00

refractive index of the sample, that can be observed by a light detector at a distance. Since its intensity depends upon optical characteristics of the sample, scanning the microstructure on the surface of the sample makes it possible to measure the optical characteristics of the sample with a spatial resolution determined by the size of the microstructure. Recently, this technology begins to be applied to a wide range of fields, such as various optical measurements, high-density optical recording, and light machining.

A near-field light probe that is most widely used is a sharply pointed optical fiber with a metal clad and having an aperture smaller than the light wavelength on a top end thereof. However, its generation efficiency of the probe is low. For example, in the case of optical fiber having a micro aperture of 100 nm, light intensity emitted from the fiber is 0.001 % or less of the light intensity having entered the fiber (1-1 Applied Physics Letters, Vol. 68, pp. 2612-2614, 1996.) This lowness of the efficiency becomes a problem when the near-field light technologies are applied to various fields.

Then, to increase the generation efficiency of the near-field light, methods that use localized plasmon excitation in metals have been proposed as in the following. That is, there are: (1) method that uses a metal probe of

10046249.014602

the scanning tunnel microscope (1-2, "Unexamined Patent Application Laid-Open, No. H06-137847"); (2) method that uses a metallic micro sphere provided on the center of the aperture of the micro aperture fiber probe (1-3, "Unexamined Patent Application Laid-Open, No. H11-102009"); (3) method that uses a probe where metal scattering members are provided on a button surface of a glass substrate (1-4, "Unexamined Patent Application Laid-Open, No. H11-250460"); (4) a method that uses triangular metal pattern provided on a flat substrate ("Unexamined Patent Application Laid-Open, No. 2000-73922" applied by the same applicant as that of this application); (5) a method that uses a quadrangular pyramid with metal films formed on two side faces thereof, (1-5 "Technical Digest of 6th International Conference on Near Field Optics and Related Techniques," the Netherlands, Aug. 27-31, 2000, pp. 100"), etc. Compared to the above-mentioned conventional arts (1) through (3), the conventional art (4) can yield intense near-field light and its fabrication is easy.

When the scattering-type probe is used, removal of background light is important as will be described later. As means for achieving this, a method whereby the probe is vibrated and only optical signal that is synchronized with the vibration is detected (6) is disclosed in "Unexamined Patent Application Laid-Open, No. H06-137847." Further, as

20040904001

another means, a method whereby a difference between amplitudes of two mutually orthogonal polarized lights is taken is disclosed in "Unexamined Patent Application Laid-Open, No. 2000-298132."

The above-mentioned conventional arts (1) through (5) each realize the generation of the intense near-field light, but contain a problem that light passes through a part other than the metallic surface and acts as the background light, which brings on decrease in the S/N (signal-to-noise) ratio of detected signal.

Use of localized plasmon excitation can increase the square of an absolute value of the electric field strength of the near-field light, namely photon density per unit area. However, the total number of photons of the near-field light, namely a value obtained by integrating the above-mentioned photon density for a localized area of the near-field light becomes not so much large because of a small area resulting from the purpose of increasing the spatial resolution.

Conversely, although the background light is small in the electric field strength, it has an area larger than the diffraction limit; therefore it is often the case that the total number of photons becomes measurably large. Assuming that the area of the near-field light is $1/S$ times the area of the background light (S) and the absolute value squared

2025-03-06

of the electric field strength of the near-field light is G times that of the background light, the total number of photons of the near-field light becomes G/S times that of the background light. For example, in the method of the above-mentioned conventional art (4), the absolute value squared of the electric-field strength of the near-field light that is localized in an area of 5 nm by 5 nm is 5700 times that of the incident light, but the area of the background light whose number of photons is equivalent to the number of photons of this near-field light becomes 380 nm by 380 nm.

This value is not more than the diffraction limit of the near-infrared laser light commonly used as a light source, and consequently, with a normal device configuration, the number of photons of the background light becomes larger than that of the near-field light. In the case where nonlinear interaction is used as in optical recording, this background light causes no problem because the interaction is affected not by the total number of photons but by the number of photons per unit area. However in the case, such as normal optical reproduction and the near-field optical microscope, where a portion of the near-field light is scattered by the sample and the amount of the light entering a detector is observed, the background light similarly enters a detector and hence the S/N ratio

10044243.011602

(signal-to-noise ratio) becomes smaller than unity. Also in the case where secondary light from the sample, such as fluorescent light and Raman light, is observed as signal light, the same problem is involved because secondary light generated by the above-mentioned background light becomes a background signal.

Up to this point, simple comparison of the number of photons in the vicinity of the sample was considered. Besides, in the above-mentioned conventional arts (1), (3), and (5), the background light is propagating light, the background light enters the detector generally with a higher degree of efficiency compared to the efficiency at which the near-field light that is non-propagating light is scattered and enters the detector placed in the distance, and hence the S/N ratio decreases further.

To solve this problem, in the conventional arts (2) and (4), the background light is suppressed by shading periphery of a metal pattern for exciting localized plasmons with an aperture having dimensions not more than the light wavelength remained. However, when dielectric materials are used as shading materials, it is difficult to achieve sufficient shading property and further problems such as generation of heat may occur.

When a metal with a high shading effect is used to avoid these problems, the following problem occurs. If there

exists a metal that has a plane parallel to a vibrating direction of the localized plasmons, an inverse electric field is generated inside the above-mentioned metal and inhibits the plasmon excitation. In other words, when a metal for shading that forms an aperture is brought close to the metal for exciting the localized plasmons, the excitation of the localized plasmons is inhibited and hence the intensity of the near-field light is decreased.

Further, depending upon the shape of the metal for shading and the direction of polarization of the incident light, the localized plasmons are excited also in the metal for shading to effect reduction in spatial resolution. Therefore, the aperture cannot be made small so much, and consequently there is a limit in improving the S/N ratio.

Moreover, since the dimensions of the excitation area of the localized plasmons are determined by the curvature of radius of a sharply pointed part of the metal, the metal top end needs to be sharpened in order to improve the spatial resolution, and for this reason the thicknesses of the metal for shading and of the metal for exciting the localized plasmons at the top end cannot be increased. Therefore, light passes through this part and becomes the background light, which presents the problem of decrease in the S/N ratio all the same.

2025-04-09 10:00:00

Moreover, in the above-mentioned conventional art (7), a method whereby the background light is removed through the use of interference of mutually orthogonal two polarized lights. However, since this method uses the scattering-type probe, a shading plate for shading the background light etc. cannot be installed due to its configuration, resulting in an increase of the absolute amount of the background light, and the wavefront of the background is deformed in consequence of the scattering by the sample and the probe as a whole; therefore it is difficult to completely remove the background light merely using interference. In addition, the surface conditions of the sample governs how the wavefront is deformed, and consequently the elimination factor of the background light is also affected by the surface conditions of the sample.

SUMMARY OF THE INVENTION

It is the object of the present invention to remove the background light presenting the problem without sacrificing the spatial resolution in optical apparatuses that use the near-field light and to provide optical apparatuses that can achieve an excellent S/N ratio.

To enhance the intensity of the near-field light, it is effective to use plasmon excitation in a metal. By using

a metal of micro dimensions, the localized plasmons can be excited and intense near-field light is generated in its periphery.

To remove the background light, a metal for shading is provided and in its opening a metal for exciting plasmons is provided. This has been disposed in the above-mentioned conventional arts (2), (4), but the present invention provides the following means to achieve an even higher S/N ratio.

The metal for shading and the metal for exciting plasmons may be the same, but if a kind and the thickness of each metal are selected, respectively, it becomes possible that the light shading property and the resolution are controlled independently. Further, the background light that has passed through either of the above-mentioned opening part or the metal thin film part is removed by the method mentioned below.

The intensity of plasmons excited in the metal having an asymmetric form as described in the above-mentioned conventional arts (4) and (5), namely the intensity of the near-field light, depends upon the direction of polarization of the incident light. On the other hand, the intensity of the background light can be deprived of its polarization dependency easily. In the case of a planar probe, adoption of normal incidence removes the

polarization dependency, and in the case of a multiangular pyramid probe, by forming metal coating thereon and controlling its thickness, the polarization dependency can be inhibited largely. Further, the polarization dependency of the intensity of the background light can be canceled out with the use of a polarization compensator that has inverse polarization dependency to this. Therefore, if the direction of polarization of the incident light is modulated and the intensity of the detected light is subjected to synchronous detection to the above-mentioned modulation, signals resulting from the background light can be removed and only the near-field light signal can be extracted.

In this invention, the probe is provided with the metal for shading to reduce the background light. In addition, the background light that leaks out even with the contrivance is removed by taking the difference of the light intensity (square of light amplitude) rather than the light amplitude.

Since the present invention does not use the interference of light, the operation of the optical apparatus is not affected by how the wavefront is deformed, and is resistant to the surface state of the sample; therefore the elimination factor of the background light to the sample can be boosted.

2009.10.24.0002

Besides, the present invention can be applied to observation of the secondary light from the sample, such as fluorescent light and Raman light. In the case where the fluorescent light of the sample is observed, since the fluorescent light generated from a part excited by the incident background light is observed as the background light in addition to the signal fluorescent light from a local part excited by the near-field light, the S/N ratio suffers deterioration. The background fluorescent light cannot be removed by means of the interference because the phase information has been lost in the fluorescent light. Since the present invention does not use the interference, the background secondary light signal can be removed for the secondary light signal from a fluorescent sample etc., and therefore can find applications in micro fluorescence spectroscopic instruments, micro Raman spectroscopic instruments, etc.

Thus, as described above, the optical apparatus that uses the near-field light according to the present invention is characterized in that it comprises: a metal member that is disposed on a substrate and has a caspidal part; a light source device for modulating the direction of polarization; an optical member for irradiating the caspidal part of the above-mentioned metal member with light from the light source device; a detector that detects light having passed

through the sample or light either reflected or scattered by the sample, which sample is illuminated with the near-field light generated from the thus irradiated caspidal part of the metal member; and a separator for extracting a signal that is synchronized with the polarization modulation from an electric signal outputted from the detector.

Further, an optical apparatus that uses the near-field light according to the present invention is characterized in that it comprises: a light source device for modulating the direction of polarization; a probe on which one or more metal members each having the caspidal part are provided; a sample stage for holding the sample; a distance controller for controlling the distance between the sample and the probe; an optical member for irradiating the caspidal part of the above-mentioned metal member with the light from the light source device; one or a plurality of detectors for irradiating the sample with the near-field light generated from the probe and detecting the signal light radiated from the sample; one or a plurality of separators for separating and detecting a signal that is synchronized with the polarization modulation of the light source device from the signal outputted from the detector(s); and a signal processor for processing the signal from the separator(s).

10046245.014602

Annotating the above-mentioned optical apparatus, the present invention gives the above-mentioned optical apparatus a construction such that the direction of polarized light that irradiates the caspidal part of the above-mentioned metal member can be switched to either linearly polarized light that is parallel to a direction of the point of the above mentioned metal member or linearly polarized light that is perpendicular to the direction of the point.

Annotating further the above-mentioned optical apparatus, the present invention gives a construction such that a polarization compensator whose transmittance or reflectance differs depending on the polarization is provided on an optical path of the above-mentioned optical apparatus, whereby the polarization characteristics of other optical components are compensated.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1(a) is a conceptual diagram of the probe and the polarization modulation method in the present invention and (b) is a conceptual diagram of the planar-type near-field light probe equipped with an anisotropic metal pattern having a micro spacing in it.

FIG. 2 is a perspective view showing one example where the present invention is applied to an optical recording/reproduction apparatus.

FIG. 3(a) is a perspective view of a cantilever having a metal pattern for exciting plasmons and (b) is a view showing a quadrangular pyramid part of a top end thereof.

FIG. 4 is a view showing the quadrangular pyramid part of the top end of the metal pattern for exciting plasmons that has a metal part for shading.

FIG. 5 is a side view of the quadrangular pyramid probe having two-step film thicknesses.

FIG. 6 is a diagram showing Au film thickness dependency of the difference between the light intensity (T_p) that is transmitted and scattered by non-blocking part of the SiN-made quadrangular pyramid probe when the p-polarized light is incident thereon and the light intensity (T_s) that suffered the same when the s-polarized light is incident thereon.

FIG. 7 is a view showing a tip of the quadrangular pyramid probe having the two-step film thicknesses that has a metal for exciting plasmons only on one lateral face thereof.

FIG. 8 is a perspective diagram of a sharply pointed optical fiber probe having the two-step film thickness structure.

FIG. 9 is a view showing an example of an apparatus configuration where the present invention is applied to the near-field optical microscope.

FIG. 10(a) is a conceptual diagram showing a construction where a plurality of probes are used and (b) is a conceptual diagram showing a different construction where a plurality of probes are used.

FIG. 11(a) is a view showing a part of the substrate where a plurality of probes are used and (b) is a conceptual diagram explaining the distance control between the substrate and the sample.

FIG. 12 is a conceptual diagram explaining an example construction that realizes the polarization modulation.

FIG. 13 is a conceptual diagram explaining another construction example that realizes the polarization modulation.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Hereafter, concrete embodiments will be described referring to the drawings.

The near-field light probes used in the present invention are roughly divided into those in a planar shape and those in the shape of a pyramid or a cone. When the sample has excellent planarity, such as a medium for optical

First, the planar probe and optical recording/reproduction device that uses it will be described. As the planer probe, a planar probe having the same metal pattern as that described in the above-mentioned conventional art (4).

FIG. 1(b) shows, as one example thereof, the near-field light probe having a triangle-shaped metal pattern on a planar substrate. Note that contraction scales in the figure are not necessarily common for all parts. A right-angle-shaped-pattern (e.g. aluminum (Al) pattern) 106 such that the radius of curvature of its top end is 20 nm and the thickness is 30 nm is formed on a glass substrate 101 of a 5 mm square so that its whole shape becomes flat. A spacing g between apexes of the two opposing triangles is set to 10 nm.

Since an irradiation area of the incident light is equal to or more than diffraction limit, if there are only patterns of the triangles, light passes through other portions and forms large background light. To shade this, the whole was covered with, for example, Al and a non-coated area 107 is provided at the apexes of the triangles and their vicinity. Since, when the non-coated area 107 becomes smaller than the light wavelength, the transmittance decreases, and when being smaller than a half-wavelength, it decreases sharply; the non-coated area 107 is set equivalent to this or less. On the contrary, if the non-coated region is set too small, it shades and attenuates the plasmons excited at the apexes of the triangles and their vicinity; therefore it needs to be set larger than a spread of the near-field light. Here the non-coated area 107 is specified as an isosceles triangle with one side of 50 nm.

A substrate 101 may be any material that has transparency to the incident light other than glasses. Further, the metal pattern 106 may be of a metal chosen from materials in which the plasmon resonance can take place. Here, the metal pattern 106 is fabricated by probe lithography, but the fabrication method is not limited to this and conventional fabrication methods different from this may be adopted.

If the direction of polarization 104 of the incident light 103 is in line with a direction A shown in FIG. 1 (a) and (b), the localized plasmons are excited at the apexes of the two opposing triangles and their vicinity and intense near-field light is generated at the gap. Conversely, if the direction of polarization of the incident light is in line with a direction B shown in FIG. 1 (a) and (b), the localized plasmons are less excited and the intensity of the near-field light generated at the gap is small. In this case, the intensity of the near-field light in the direction A is approximately 1000 times that in the direction B.

The substrate on which the sample is mounted or a recording medium 102 is disposed opposing to the metal pattern of the probe and a distance between the probe and the sample or the recording medium 102 is controlled to be less than λ . The near-field light generated at the apexes of the two opposing triangles and their vicinity is converted into propagating light 105 through interaction with the sample or the recording medium 102. The propagating light 105 also includes light leaking from the non-coated area 107, namely the background light, besides the scattered light of the near-field light. The scattered light of the near-field light reflects optical property of a micro area of the sample or the recording medium 102. If the direction of polarization 104 is modulated between the directions A

20250310 04:50:00

and B, the scattered light of the near-field light varies largely but the background light exhibits no change. Thereby the propagating light 105 is observed in synchronization with the polarization modulation and only the scattered light of the near-field light is separated and observed.

Here the metal pattern in which the two triangles oppose each other is illustrated, but the present invention can be applied to other probes and apparatuses similarly.

FIG. 2 shows is one embodiment in which this invention is applied to an optical recording/reproduction apparatus. A planar probe 201 according to this invention shown in FIG. 1 is mounted on a suspension 202 and is pressed to the recording disk 203. An actuator 204 is used for fine adjustment of the position for tracking. Light emitted from a diode laser 205 passes through a collimator lens 206 and a beam reshaping prism 207, and subsequently is guided to a polarization modulator 208, where its direction of polarization is switched to either the direction A or the direction B. After that, the light is focused on the planar probe 201 by a half mirror 209 and an objective lens 210.

Positioning of the objective lens 210 in a focusing direction is done by an actuator 211. The above-mentioned components except the recording disk 203 are all arranged on a slider as constituent members of an optical head, and the position of the optical head is controlled by an actuator

20040450100

for coarse tracking in the same manner as the normal optical head.

When performing the recording, record marks are formed on the recording disk 201 by directly modulating the intensity of the diode laser 205. At this time, the polarization modulation by the polarization modulator 208 is stopped and the linearly polarized light is fixed so that the direction of polarization lies in the direction A. As another recording method, the intensity of the near-field light may be modulated by changing the direction of polarization with the polarization modulator 208 according to recording signals. In other words, the direction of the linearly polarized light is set in the direction A when the record mark is to be recorded; it is set in the direction B when the record mark is not to be recorded.

When performing the reproduction, presence and absence of the record mark on the recording disk 203 causes the scattering efficiency of the near-field light to be varied, and accordingly the intensity of light that returns to a direction of reflection is varied. This light is detected by a detector 213 using a focusing lens 212, is converted into the electric signal, and subsequently is inputted into the lock-in amplifier 214. At this time, a driving signal of the polarization modulator 208 is used as a reference signal. Since the intensity of the near-field

light is modulated in synchronization with the polarization modulation, the intensity of the scattered light of the near-field light by the record mark varies in synchronization with this and is detected as a signal by the synchronous detection. However, since the background light in the case of normal incidence does not depend on the direction of polarization, the component of the background light included in the signal of the reflected light is removed by the synchronous detection.

Thus, only the reproduction signal is extracted, and then the signal is sent to a signal processing circuit 215. Practically, since each of optical components, starting with the half mirror 209, has polarization dependency in its transmittance, the background light signal cannot be removed only by the synchronous detection. Therefore, a polarization compensator 216 is provided and its inclination is set so that the background light becomes the minimum. This is because the transmittance of a glass plate that is disposed with its normal inclined to the optical axis has different transmittances for s-polarized light and for p-polarized light and the difference between them depends on the incident angle, and hence, by choosing an appropriate incident angle, the polarization dependency of the transmittance or reflectance of each of the above-mentioned

100-10-01-000

optical components can be canceled out, acting as the polarization compensator.

Here the glass plate that was disposed slantingly was used as the polarization compensator. A dielectric multilayer film that is normally used as a polarization filter, a material having different absorption for different direction of polarization, for example a film that was doped with a dye and stretched in one direction, etc. may be used. The above-mentioned method whereby the signal light is separated and detected in synchronization with the polarization modulation of the incident light will be hereinafter referred to as "polarization modulation and synchronous detection method."

With wider apex angles of the triangular caspidal parts of the probe shown in FIG. 1, the intensity of the near-field light tends to be more intense. However, this apex angle has the highest S/N ratio when it is 90 degrees because of the following reason.

At any edge parts of the metal other than the apexes of the triangles where the localized plasmons are excited, enhancement of the near-field light by the surface plasmons occurs. When the direction of polarization of the light is orthogonal to the edge, this enhancement becomes maximum; when it is parallel to the edge, the enhancement becomes zero. Although the intensity of the near-field light at the

10046245-014602

edge parts is smaller than the intensity of the near-field light at the apexes by a few orders, but the area of the edge parts is large and that the intensity of that near-field light has polarization dependency, so normally the component of its scattered light cannot be removed completely only by the above-mentioned synchronous detection. However, if the apex angles of the triangles are set to 90 degrees, both of the polarized light whose direction of polarization lies in the direction A in FIG. 1 and the polarized light whose direction of polarization lies in the direction B have equivalent components each projected to a direction orthogonal to each edge and hence the intensities of the near-field light at the edge parts become equivalent; therefore these components can be removed by the synchronous detection. Therefore, when the near-field light generated at the edge parts of the triangles interrupts the measurement, it is recommend that the apex angles of the triangles be set to 90 degrees.

In this embodiment, an application of the invention to the optical recording method was described. However, this invention can also be applied to the opto-magnetic integration method. Further, in this embodiment, the light detector is provided in a direction of regular reflection, but the light detector may be provided in a direction of transmittance or in a lateral direction.

10046245-041502

A lubricant may be applied between the metal pattern of the probe and the recording medium. Further, by providing a thin film layer of a dielectric material or a semiconductor that transmits the incident light, for example, a glass etc., on a plane where the metal pattern of the probe was provided, it is possible to protect the head and the recording material and to control the distance of the metal pattern.

Next, a pyramidal probe will be explained. In FIG. 1 the metal pattern of the triangles was provided on the planar substrate, but it is recommended to provide the same pattern on a caspidal part of an acicular member in order to enable the probe to accommodate the unevenness of the sample. For such an acicular member, the one in the shape of a cone such that a point of an optical fiber is sharpened by using a method of chemical etching or heat stretching or the one in the shape of a pyramid (shape of a multiangular pyramid) as the probe for the atomic force microscope may be used. In the microscopic instruments, such as the micro fluorescent spectroscopic instrument and the micro Raman spectroscopic instrument, wavelengths of the incident light and of the signal light do not necessarily agree with each other. For the above-mentioned acicular member, a material that has transparency at least to either of the incident light or the signal light should be used.

10046249 044602

FIG. 3 shows a cantilever 300 made of SiN for the atomic force microscope on whose top end 301 a metal 302 was evaporated. Al was used for a metal. Here only two faces that oppose each other are provided with the metal film by means of evaporation from two directions, but only one face may be processed so. Further, in FIG. 3, a configuration where no gap exists at top ends of the metal films on the two opposing faces. Even with this configuration, intense near-field light is generated on side faces at the apexes and their vicinity. Needless to say, a gap may be provided at the apexes in the same manner as FIG. 1.

The structure described up to this is the same as the pyramidal probe described in the conventional art (5). However, with the structure as described, it is difficult to achieve a sufficient S/N ratio because the light passing through faces that were not covered with the metal forms large background light.

As the simplest solution, there is a method of covering other faces with a metal for shading 401 as shown in FIG. 4. However, since the metal for shading becomes parallel to a vibration direction of the electric field of the plasmons and weakens this, it must be separated at least from an excitation area of the plasmons. Therefore, non-coated parts 402 are provided on the top end of the metal for shading in FIG. 4. If the light passes through these

parts, it becomes the background light. To suppress this phenomenon, the non-coated parts 402 must be smaller than a half-wavelength of the said light. Even taking such a measure, there remains an opening anyhow, so that the light passes therethrough without fail; therefore the background light cannot be removed completely.

In addition, in the case of the acicular probe, there is another factor that makes removal of the background light incomplete as shown in the following. To improve spatial resolution of the apparatus, it is necessary to reduce the radius of curvature of the metal part at the top of the probe, and for this purpose it is necessary to thin the thickness of metal at the top end to be equivalent to or less than the radius of curvature. If the thickness of metal is too thin, sufficient shading performance cannot be attained and the light passing through the metal part becomes the background light.

To solve this problem, the thickness of metal is specified to be two levels as shown in FIG. 5. In other words, the metal thickness is thinned only for a top end 501, whereas the thickness of metal is ensured to be thick so as to attain sufficient shading property for a part other than the top end 502. The length of the top end 501 having the thin film should be as short as possible to suppress the background light and a half the wavelength of the said light

10010210-011002

or less is desirable. However, to allow the probe to track the unevenness of the sample under observation, the length of the top end 501 having the thin film must be set to be longer than undulation of the unevenness; therefore the background light cannot necessarily be suppressed sufficiently.

As described in the foregoing, the background light can be suppressed with a structure of the probe but cannot be removed completely. Naturally, there are some applications for which the probe structure only with the above-mentioned contrivance suffices. However, for applications that requires especially high spatial resolution and for cases where the probe is applied to samples with considerable unevenness, a sufficient S/N ratio may be not attained, and consequently it is recommended to adopt the polarization modulation and synchronous detection scheme as is the case of the planar probe mentioned above.

Further, if the polarization modulation and synchronous detection scheme is combined with the contrivance of the probe structure shown in FIG. 4 and FIG. 5, an even higher S/N ratio can be achieved. However, since the transmittance of the acicular member is different for s-polarized light and for p-polarized light, respectively, this difference must be compensated to suppress the background light

10046245 041602

FIG. 6 shows dependency of the difference ($T_p - T_s$) between the intensity of the transmitted and scattered light for p-polarized light (T_p) and the intensity of the transmitted and scattered light for s-polarized light (T_s) on the metal thickness for the case where SIN is used for the acicular member and gold (Au) is used for the metal film. In this case, if the film thickness of gold is chosen to be 7 nm or 15 nm, the polarization dependency of the intensity of the transmitted and scattered light is taken away, hence the said synchronous detection scheme becoming capable of removing it. Since this film thickness depends upon the complex refractive indexes of the acicular member and the metal, the film thickness must be chosen appropriately for materials to be used. For example, when SIN is used for the acicular member and Al is used for the metal, the optimum value becomes approximately 3 nm. If the film thicknesses of the above-mentioned metal for exciting plasmons and of the metal for shading are set to the said film thickness, the background light can be removed by the synchronous detection scheme; therefore this method has an effect of simplifying the probe structure. To obtain an even higher S/N ratio, it is recommended that a thin portion of the top

end 501 of the above-mentioned two-step film thickness probe be set to the said film thickness. Alternatively, independent from or in combination with these contrivances, the above-mentioned polarization compensator may be used.

If such a structure as in FIG. 5 is adopted, the plasmons are excited by the light polarized in the direction A at the metal tip for exciting the plasmons 505 of the top end 501. On the other hand, for the light polarized in the direction B, the plasmons are inevitably excited at a metal end part 506 provided for shading. If the plasmons generate the signal light, the detected signal by the polarization modulation and synchronous detection scheme is decreased. To cope with this, it is necessary to take the length of the top end 501 enough with the intention of separating the sample from the metal for shading sufficiently. Still, it might not be avoided that both members become near because of the unevenness of the sample.

To solve this problem, a material having such a property that generation efficiency of the plasmons at the said light wavelength is lower than that of the metal for exciting plasmons should be chosen. For example, it is appropriate to use Al as the metal for exciting plasmons and use Au as the metal for shading for light having a wavelength of 400 nm. Naturally, for applications where the above-mentioned problems can be ignored, the same metal can

10046249-0146002

be used for the metal for exciting plasmons and the metal for shading. Such cases have an effect that the cost can be curtailed because the fabrication of the probe becomes relatively easy.

FIG. 7 and FIG. 8 show other embodiments of the acicular probe. FIG. 7 illustrates a probe fabricated by providing a metal for exciting plasmons 701 only on a single face of the above-mentioned quadrangular pyramid, and FIG. 8 illustrates a probe fabricated by evaporating a metal for exciting plasmons 801 on a half cone surface of the sharply pointed optical fiber.

Note that structures shown in FIG. 7 and FIG. 8 are only examples. For the pyramidal probe and the conical probe, two of the metal for exciting plasmons may be opposed as show in FIG. 4, the pyramid or cone may be covered with the metal up to a top of that subulate geometry as shown in FIG. 8, or there may be a slight gap between the metal parts as shown in FIG. 7. Moreover, for all the structures described, a kind and the thickness of the metal for shading and those of the metal for exciting plasmons may be changed or may be unchanged. These variants may be used properly according to applications of use and the cost.

Next, a fabrication method of the above-mentioned probe will be described. When only one side of the acicular member is provided with the metal, the metal was evaporated

2025 RELEASE UNDER E.O. 14176

only from one direction. When the non-coated part is provided at the top and its vicinity and when the two-step film thicknesses are formed, the following procedures were used.

First, a target face (or side) of the acicular member is provided with the metal thin film by the above-mentioned method. Photoresist is applied on that part and left with the end part turned up, and thereby the film thickness of the resist at the end part becomes thin. Subsequently, when the resist is subjected to a baking process and dry etched, the metal begins to be etched from the end part where the resist film thickness is thin. By properly adjusting the etching time, the length of the nonmetal coated part can be controlled. When the two-step film thicknesses are intended to be made, the metal that acts as a metal for exciting plasmons at the said wavelength is formed and then a different kind of metal for shading is evaporated thereon. Subsequently, the probe is subjected to a resist-etching process by the same method as described above. In this process, if an etching gas that has a fast etching speed for the metal for shading but has a slow etching speed for the metal for exciting plasmon, only the metal for shading is removed at the top end, so that the two-step film thicknesses can be realized. Further, if first the metal for shading is provided also on a face other than the face where the metal

2025 RELEASE UNDER E.O. 14176

for exciting plasmon was provided and second the film thickness and the etching time of the two kinds of metals in the above-mentioned method are properly chosen, then the structure that has both the two-step film thicknesses and the non-coated part, shown in FIG. 5, can be manufactured.

Here, for the acicular member, a cantilever made of SIN for the atomic force microscope was used. First, on the opposing two faces, Al was evaluated for a 10 nm thickness as the metal for exciting plasmons, and then W was evaporated for a 100 nm thickness as the metal for shading over all faces. Etching was conducted with CF_4 gas in the above-mentioned procedures to fabricate the structure of FIG. 5.

Next, referring to FIG. 9, one embodiment where the polarization modulation and synchronous detection scheme was applied to the near-field optical microscope will be described. A sample to be measured 903 is placed on a transparent substrate 902 that was disposed on a scanning stage 901 capable of the three-dimensional position control. A cantilever-type probe 904 that has metal parts at the end part as mentioned above is disposed so as to face the sample. Here, position control is done using the dynamic force method that is commonly used in the probe microscope and the distance between the sample 903 and the probe 904 is controlled to be approximately 5 nm. For this purpose,

the probe 904 is vibrated in the vertical direction using a dither piezo 905. Note that a laser and a split photodiode that are used to observe the probe vibration and an optical system associated with this are things already known, and hence are not shown in the drawings.

The distance between the sample and the probe needs to be set not more than the length of permeation of the near-field light, so that the two members may be contacted with each other. For the distance controlling method, other methods that are normally used in the probe microscope, such as the tunnel current controlling method and the optical lever method, may be used. Especially, since this invention does not need such vibration of the probe to remove the background light as needed by the conventional art (6), it has an effect of circumventing both decrease in the resolution associated with the probe vibration and complication of an observed image associated with inclusion of false signals on condition that a method for controlling the distance that requires no vibration of the probe is adopted at the same time.

Output light of a diode laser 907 is collimated by a lens 908, its direction of polarization is switched to the direction A and the direction B, as shown in FIG. 5, at regular intervals by a polarization modulator 909, and after being transmitted through a polarization compensator 910,

10045245-01602

it is guided to the top of the probe 904 by an objective lens 911. The sample 903 is illuminated with the intense near-field light generated at the top of the probe to radiate the signal light.

Here an example where the transmitted light of the sample is detected as the signal light is shown. The transmitted light is guided to a light detector 921 by a lens 920, being converted into the electrical signal, and is subjected to the synchronous detection by a lock-in amplifier 930. A reference signal at the time of the detection is obtained from the polarization modulator 909. An output of the lock-in amplifier 930 is fed into a controller 931. The sample plane is scanned with the aid of the scanning stage 901, the output of the lock-in amplifier 930 is measured at each position, and the output signals are converted into an image by using the controller 931 that doubles as an image processing apparatus, and thereby the optical signal image of the sample can be obtained. Representing the frequency of the polarization modulation by a symbol f and a time constant of the synchronous detection by a symbol T , f is set to be sufficiently larger than $1/T$.

Note that in FIG. 9 a mechanism for observing the sample position is omitted but that an illumination system as used in the normal microscope and an observation system

This embodiment uses the transmitted light as the signal light. However the present invention can be applied to other microscopic instruments that use other light than the transmitted light. Even in the case where the signal light is one of reflected light, scattered light, florescent light, Raman light, etc., the similar measurement can be performed on condition that optical components used normally, a spectroscope, etc. are attached thereto. Further, in the case where the sample exhibits macroscopic anisotropy and the intensity of the background light-induced fluorescent light differs for polarization, a polarization compensator may be adjusted so that such inequality becomes minimum.

Moreover, in the case where photoconductivity of the sample is measured, a photoconductive signal should be subjected to the synchronous detection by the lock-in amplifier 930.

In this embodiment, the incident light is guided to the probe to irradiate the sample and the signal light propagating in a direction of transmission is detected. However, other illumination and detection configuration that is normally used in the near-field optical microscope may be used. In other words, one of the following configurations may be used: (1) configuration where the incident light is guided to the probe to irradiate the sample and the signal light radiated in a direction of reflection is detected; (2) configuration where the incident light is guided to the probe to irradiate the sample and the signal light returning to the probe is detected; and (3) configuration where a top end of the probe is illuminated from the outside and the signal light entering the probe is detected. In the configuration where the incident light is guided to the probe to irradiate the sample and the signal light returning to the probe is detected, reflected light from various faces of the probe generally forms large background light, and hence the present invention becomes useful especially.

Further, in the case of measurement where the probe is not made to follow the unevenness of the sample, the planar probe shown in FIG. 1 may be used.

Next, a further embodiment according to the present invention will be described. The probe used in the present

invention is easy to fabricate and its fabrication method is easy and gives high reproducibility compared to the heat drawing method etc. Therefore, multi probes can be arranged easily.

FIG. 10(a) is an example where four planar probes are arranged. Four patterns shown in FIG. 1 are arranged on the substrate 1000. At this time, centers of the probes 1001 to 1004, namely locations where the near-field light is generated, are arranged so as to be separated from each other by a distance larger than diffraction limit. Incident light 1005 is polarization-modulated, irradiates the probe so that the centers of the probes are irradiated uniformly, and is imaged on an image plane 1007 to form an enlarged image of a plane of the probe, using an optical system 1006. On centers of the image of the probe's centers so obtained, detectors 1011 to 1014 are arranged, and each output of the detectors is detected synchronously with lock-in amplifiers. Being omitted in the drawing, the subject under measurement is placed between the substrate 1000 and the optical system 1006. Other points are the same as the above-mentioned embodiment.

Here, a configuration where single incident light 1005 is used to illuminate all the probes is used. However each probe may be illuminated with separate incident light or each group of plural probes is illuminated with separate

2025.04.04 10:40:00

incident light. Alternatively, the incident light may be scanned to illuminate the probes therewith sequentially. Here, the embodiment where four probes were used was described, but much more probes may be formed according to applications. In such a case, the light detectors of the same number should be prepared for the respective probes.

The light detectors 1011 to 1014 in FIG. 10(a) may be replaced with a single image pickup tube. With this replacement, signal lights from the centers of the probes can be detected at the same time. At this time, if the control signal for polarization modulation of the incident illumination light is synchronized with a vertical synchronizing signal of the image pickup tube, the signal caused by incident polarized light whose direction of polarization is orthogonal to that of an adjacent frame is detected; therefore the background light can be removed by operating subtraction between the signals of adjacent frames. Although this scheme provides lesser improvement effect of the S/N ratio compared to the case with the use of a lock-in amplifier, simplification of the apparatus and curtailment of the cost become possible.

FIG. 10(b) shows another example of an apparatus's construction where a plurality of probes are used. Here, to simplify the drawing, a case where two probes are used is shown. Two beams of light from light sources (not shown in

1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2813 2814 2815 2816 2817 2818 2819 2820 2821 2822 2823 2824 2825 2826 2827 2828 2829 2830 2831 2832 2833 2834 2835 2836 2837 2838 2839 2840 2841 2842 2843 2844 2845 2846 2847 2848 2849 2850 2851 2852 2853 2854 2855 2856 2857 2858 2859 2860 2861 2862 2863 2864 2865 2866 2867 2868 2869 2870 2871 2872 2873 2874 2875 2876 2877 2878 2879 2880 2881 2882 2883 2884 2885 2886 2887 2888 2889 2890 2891 2892 2893 2894 2895 2896 2897 2898 2899 2900 2901 2902 2903 2904 2905 2906 2907 2908 2909 2910 2911 2912 2913 2914 2915 2916 2917 2918 2919 2920 2921 2922 2923 2924 2925 2926 2927 2928 2929 2930 2931 2932 2933 2934 2935 2936 2937 2938 2939 2940 2941 2942 2943 2944 2945 2946 2947 2948 2949 2950 2951 2952 2953 2954 2955 2956 2957 2958 2959 2960 2961 2962 2963 2964 2965 2966 2967 2968 2969 2970 2971 2972 2973 2974 2975 2976 2977 2978 2979 2980 2981 2982 2983 2984 2985 2986 2987 2988 2989 2990 2991 2992 2993 2994 2995 2996 2997 2998 2999 3000 3001 3002 3003 3004 3005 3006 3007 3008 3009 3010 3011 3012 3013 3014 3015 3016 3017 3018 3019 3020 3021 3022 3023 3024 3025 3026 3027 3028 3029 3030 3031 3032 3033 3034 3035 3036 3037 3038 3039 3040 3041 3042 3043 3044 3045 3046 3047 3048 3049 3050 3051 3052 3053 3054 3055 3056 3057 3058 3059 3060 3061 3062 3063 3064 3065 3066 3067 3068 3069 3070 3071 3072 3073 3074 3075 3076 3077 3078 3079 3080 3081 3082 3083 3084 3085 3086 3087 3088 3089 3090 3091 3092 3093 3094 3095 3096 3097 3098 3099 3100 3101 3102 3103 3104 3105 3106 3107 3108 3109 3110 3111 3112 3113 3114 3115 3116 3117 3118 3119 3120 3121 3122 3123 3124 3125 3126 3127 3128 3129 3130 3131 3132 3133 3134 3135 3136 3137 3138 3139 3140 3141 3142 3143 3144 3145 3146 3147 3148 3149 3150 3151 3152 3153 3154 3155 3156 3157 3158 3159 3160 3161 3162 3163 3164 3165 3166 3167 3168 3169 3170 3171 3172 3173 3174 3175 3176 3177 3178 3179 3180 3181 3182 3183 3184 3185 3186 3187 3188 3189 3190 3191 3192 3193 3194 3195 3196 3197 3198 3199 3200 3201 3202 3203 3204 3205 3206 3207 3208 3209 3210 3211 3212 3213 3214 3215 3216 3217 3218 3219 3220 3221 3222 3223 3224 3225 3226 3227 3228 3229 3230 3231 3232 3233 3234 3235 3236 3237 3238 3239 3240 3241 3242 3243 3244 3245 3246 3247 3248 3249 3250 3251 3252 3253 3254 3255 3256 3257 3258 3259 3260 3261 3262 3263 3264 3265 3266 3267 3268 3269 3270 3271 3272 3273 3274 3275 3276 3277 3278 3279 3280 3281 3282 3283 3284 3285 3286 3287 3288 3289 3290 3291 3292 3293 3294 3295 3296 3297 3298 3299 3300 3301 3302 3303 3304 3305 3306 3307 3308 3309 3310 3311 3312 3313 3314 3315 3316 3317 3318 3319 3320 3321 3322 3323 3324 3325 3326 3327 3328 3329 3330 3331 3332 3333 3334 3335 3336 3337 3338 3339 3340 3341 3342 3343 3344 3345 3346 3347 3348 3349 3350 3351 3352 3353 3354 3355 3356 3357 3358 3359 3360 3361 3362 3363 3364 3365 3366 3367 3368 3369 3370 3371 3372 3373 3374 3375 3376 3377 3378 3379 3380 3381 3382 3383 3384 3385 3386 3387 3388 3389 3390 3391 3392 3393 3394 3395 3396 3397 3398 3399 3400 34

SECRET

A light signal from the subject under measurement 1066 is subjected to photoelectric conversion by the single detector 1070 and subsequent branching, and is detected synchronously by lock-in amplifiers 1081 and 1082. Here, the subject under measurement means, for example, the actual sample or the substrate on which the sample is mounted. Since the lock-in amplifiers conduct synchronous detection using reference signals from corresponding polarization modulators, respectively, outputs from the lock-in amplifiers 1081 to 1084 correspond to light signals from the centers of the probes 1001 to 1004, receptively. With this arrangement, the detectors can be unified to one detector, hence enabling miniaturization of the device.

Here the embodiment with the two probes was described. Much more probes may be formed according to applications in the same manner as the above-mentioned embodiment.

If a plurality of probes are arranged on a single slider, the speed of the reproduction of light can be enhanced. To enhance the speed of the optical recording as well, there may be adopted a configuration where the same number of the incident light sources as the probes are prepared and each light source is made capable of irradiating each center of the probe independently, which enables independent writing.

Further, if the multi probes described in this embodiment are applied to a microscopic instrument, measurement and observation of a large area can be performed in a short time. For example, this scheme can be used in microscopes, micro-spectroscopic instruments, the optical lithography, optical processing equipment, etc. A scheme of position control in this case is shown in FIG. 11.

In FIG. 11(a), a substrate 1000 with multi probes arranged thereon is fixed to a supporting plate 1150. On three points of the supporting plate 1150, metal needles 1151 to 1153 are provided. These needles each are made of a probe of a tunnel microscope and are applied with a tunnel current to enable measurement, respectively. These needles are disposed on piezo-electric actuators 1161 to 1163,

respectively, and are capable of adjusting their lengths protruding from the substrate separately.

In FIG. 11(b), first the metal needles 1151 to 1153 are set not to protrude beyond a bottom surface of the substrate 1000 and the substrate 1000 is brought to adhesion on a flat sample 1170. Under this condition, the voltages applied to the piezo-electric actuators 1161 to 1163 are adjusted so that the tunnel currents following in the metal needles 1151 to 1153 become equal. Next, a constant bias voltage is added to the voltages having been applied to the piezo-electric actuators 1161 to 1163 to cause the metal needles to protrude from the substrate. The previously determined tunnel currents are specified as set values, and then the voltages applied to the piezo-electric actuators 1181 to 1183 are controlled so that the tunnel currents of the metal needles 1151 to 1153 become always the set values, respectively. The piezo-electric actuator 1183 is not shown in the figure but is arranged in the same manner as the piezo-electric actuators 1161 to 1163, so that an elevation angle of the sample 1170 can be adjusted using three support parts. The distance between the sample and the substrate is adjusted with the above-mentioned set values of the bias voltage and the tunnel current. With this arrangement, the stage 1171 carrying the sample thereon can be scanned while parallelism between the flat sample 1170 and the substrate

100462400
20970

1000 is maintained. The stage 1171 has a hole 1172 that enables the objective lens 920 for condensing the transmitted light to access the flat sample 1170.

Here the piezo-electric actuators 1161 to 1163 are used to adjust the protruding lengths of the metal needles 1151 to 1153. However, use of metal spheres having the same particle size instead of the metal needles eliminates the provision of the piezo-electric actuators 1161 to 1163. Further, in this embodiment, the planar probe was described, but a plurality of pyramidal or conical probes may be arranged instead.

For multi point observation of a sample having poor flatness, a Si thin film substrate is suitable as the substrate on which multi probes are arranged. This has a merit that adhesion with the sample can be improved because it allows light in a visible radiation range to pass through and is flexible as well. When performing a measurement, a voltage is applied between the sample and the patterns of the metal for exciting plasmons and the metal for shading to effect adhesion between them. Subsequently, the applied voltage is turned off, the sample is scanned, and the position is changed to perform next measurement. Other points of the construction and procedures are the same as those of the above-mentioned embodiment, and explanation will be omitted.

20040401.01.0002

Furthermore, for multi point measurement of a sample having even worse flatness, it is recommended to adopt a construction where a plurality of cantilevers that each have a pyramidal or conical probe as shown in FIGS. 3, 4, 5, 7, and 9 or those that each have a planar pattern shown in FIG. 1 in a previously flattened part at the top of the subulate part are arranged and the distance between each cantilever and the sample is controlled independently. For the distance control between the individual cantilever and the sample, well know schemes, such as the optical lever scheme and the dynamic force scheme, should be employed. Note that in this case, the sample is not moved as in the case of the above-mentioned embodiment for the distance control but a construction is adopted where the cantilever side is moved. Moreover, alternatively, if the sample is pressed to the cantilever without actively conducting the distance control, all the cantilevers can be made contact with the sample through manipulation of respective cantilevers even in the case where the sample has the unevenness. Note that for members for absorbing the unevenness of the sample, the cantilever is not necessarily needed but any member having a spring mechanism may be used.

When a multi-point probe is used, image data whose spatial resolution is much the same as the distance between the probes, namely, the diffraction limit of light in the

present case, can be obtained even without scanning the sample or the substrate. Therefore, the sample can be observed beforehand with low resolution and hence this case has a merit that an interested part can easily be found.

In the embodiments described up to here, the polarization modulator that uses electrooptic effect was used to modulate the polarization of the incident light, but other well-known methods such as a photoelastic modulator and a rotating half-wavelength plate may be used. Further, the polarization modulation is conducted to switch the two directions of the linearly polarized light, but the linearly polarized light may be rotated continuously.

However, these polarization modulators normally have large sizes and require application of high voltages or driving devices. Therefore, they have higher costs and are difficult to be miniaturized, which may become a problem especially when being used in the optical recording/reproduction apparatuses. Here, referring to FIG. 12, an example of polarization modulation means that is intended to hold down the cost and realize space saving will be described.

A diode laser 1201 and a diode laser 1211 are arranged so that directions of linear polarization of the two output lights 1204, 1214 become orthogonal to each other. Two beams of the output light pass through collimator lenses 1202,

1203, 1212, 1213

1212 and beam reshaping prisms 1203, 1213 and subsequently are guided to the same light path by a polarizing beam splitter 1220. It becomes possible to switch the direction of polarization by shifting phases of signals 1205 driving the diode laser 1201 and of signals 1215 driving the diode laser 1211 by 180 degrees and switching the diode laser 1201 and the diode laser 1211 alternately.

Here, the diode lasers are used, but any laser that can switch the output alternately or that is equipped with a mechanism whereby the switching can be conducted with the use of an external intensity modulator or a shutter may be used. An example of this is shown in FIG. 13.

In this scheme, a single laser 1300 of linear polarization is used rather than preparing a plurality of diode lasers. Output light of the laser 1300 is branched into two parts with the beam splitter 1301, the polarization of one part is rotated by 90 degrees using a half-wavelength plate 1302, and then the two parts are interposed on the same axis using the polarizing beam splitter 1220. A light chopper 1303 is made to have such a blade configuration that when the one of two parts of the light passes through it, the blade blocks the other part, so that the two parts are allowed to pass therethrough alternately. With this embodiment, an inexpensive measurement instrument can be constructed.

20040401 10:40:00

Further, by combining the optical pulse trains from the two mode-locked lasers that have mutually-orthogonal linearly-polarized light and lase at a synchronized repetition frequency so that light pulses from the one laser are interposed between those from the other laser, there can be obtained light whose direction of polarization was modulated similarly.

Furthermore, in the embodiments described in the foregoing use the lock-in amplifier to extract a signal component that is synchronized with the polarization modulation. However, for a simple configuration, a frequency filter that allows the modulation frequency to pass through may be used to extract it, which is subsequently amplified and rectified. This variant is effective, especially for an optical recording/reproduction apparatus that is required to be low-cost and space-saving.

According to the present invention, in the optical apparatuses that use the near-field light, compatibility between achievement of high resolution and improvement of the S/N ratio that are normally in a trade-off can be realized.